



KEY FEATURES

- 4 leg heavy duty construction
- 5MT spindle accepts standard drills & tooling
- Variable auto / hand feed
- Fast mount system and centre locator
- Hydraulic and pneumatic drive options

DESCRIPTION

The Mirage HT60VF is a versatile portable drilling and boring machine with a variable feed.. The machine can be bolted directly to the work piece, or fixed using either optional switch magnets or chain clamps for pipe mounting.

APPLICATIONS

For multi-purpose drilling and stud removal applications on-site. The various fixing methods available enable the machines to be used for a wide range of drilling jobs in any orientation.

SPECIFICATIONS

| | | |
|---|-----------|------------|
| Max Hole Diameter (through base) | 152mm | 6” |
| Max Standard Stroke | 450mm | 17” |
| Max Optional Stroke | 610mm | 24” |
| Spindle Type | 5MT | |
| RPM Min Max | 5 | 60 |
| Drive Output Pneumatic @ 6 Bar | 4.0Hp | 3.0kw |
| Drive Output Hydraulic @ 70 Bar | 5.0Hp | 3.7kw |
| Air Consumption Required @ 90psi | 2.7m3/min | 98 cfm |
| Hydraulic Supply Needed | 50L/min | 13 Gal/min |

FEED RATES

| | | |
|--|----------|-------------|
| Hand Feed per rev | 2.5mm | (0.100”) |
| Variable auto-feed per min (optional) | 0 - 32mm | (0 – 1.25”) |

INCLUDED AS STANDARD WITH MACHINE


The machine is supplied complete with the following items;

- ✓ Toolkit
- ✓ Air filter lubricator (Pneumatic models)
- ✓ Hose connection
- ✓ Storage / shipping box
- ✓ CE certificate,
- ✓ Packing list and manual

SET UP AND OPERATION

The operator must be:

- Trained and conversant with the product
- Able to identify the correct and incorrect use of static or portable machines.
- Comply with all local and internationally recognised safe use of powered machines.



MACHINE WEIGHT

87 kg

191 lb

SHIPPING WEIGHT

123kg

191 lb

SHIPPING DIMENSIONS

| Length | Width | Height |
|-------------|------------|------------|
| 115cm (45") | 42cm (16") | 50cm (20") |